

Stand-alone prox card lock

Specification

- Keycard:Mifare card(13.56MHZ)
- Power:4xAA Alkaline batteries
- Status Power consumption:<25μA
- Operating Power consumption:<150μA
- Working temperature:-20°C~ +85°C
- Working humidity:20%~98%
- Lock Management software:English,Spanish
- Low Voltage warning: <4.8V warning signal,can still operate 50 times
- Memory:Recording 920 signals
- Mechanical lock:Emergency open
- Door thickness:38mm~60mm,call for Special door

Ordering Information

<u>SHL-100-SB</u>	Slick style,Satin Brass
<u>SHL-100-SC</u>	Slick style,Satin Chrome
<u>SHL-100-C</u>	Slick style, Chrome
<u>SHL-100-G</u>	Slick style,Gold
<u>SHL-200-SB</u>	Heavy duty, Satin Brass
<u>SHL-200-SC</u>	Heavy duty, Satin Chrome
<u>SHL-200-C</u>	Heavy duty, Chrome
<u>SHL-200-G</u>	Heavy duty,Gold
<u>SHL-200-PC</u>	Heavy duty,Pure Copper
<u>SHL-300-SB</u>	Stylish, Satin Brass
<u>SHL-300-SC</u>	Stylish, Satin Chrome

Distributed by

SSI Security
Solution
inc.