

# Lock-set Series



SML-1200

## Magnetic Locks & Strikes Locks

We are the manufacturer and supplier of locking solutions and associated products, dedicated to satisfying end-user needs for security, safety and convenience.



SML-600



SSL-200A



SSL-200B

# Magnetic Locks & Strikes Locks

## Specification

MODEL	SML-1200	SML-600
Description	Magnetic Lock-1200 Pounds	Magnetic Lock-600 Pounds
Magnet size	10 1/2" x 1 5/8" x 2 5/8" (268 x 42 x 67mm)	9 7/8" x 1 1/16" x 1 5/8" (250 x 27 x 42mm)
Armature size	7 1/4" x 5/8" x 2 3/8" 185 x 16 x 61mm	7 1/4" x 1/2" x 1 1/2" 185 x 12 x 38mm
Holding force	1200lb (545kg)	600lb (272kg)
Current Drain	500mA/12VDC, 250mA/24VDC	500mA/12VDC, 250mA/24VDC
Voltage Tolerance	(+/-)10%	(+/-)10%
Temperature	(-10 <sup>o</sup> to 55 <sup>o</sup> )C (14 <sup>o</sup> to 131 <sup>o</sup> )F	(-10 <sup>o</sup> to 55 <sup>o</sup> )C (14 <sup>o</sup> to 131 <sup>o</sup> )F
Unit Weight (Approx.)	10.46lb. (5.0 kg)	4.26lbs. (2.0 kg)

## Specification

MODEL	SSL-200A	SSL-200B
Description	Electric Door Strike lock-Fail-secure	Electric Door Strike lock-Fail-safe
Type	Fail Secure	Fail Safe
Circuit Type	N.O.	N.C.
Input Voltage	10-14VDC	10-14VDC
Current	800mA	165mA
Coil Resistance	14 ohm	76 ohm
Polarity	None	None
Weight	350g	350g

\* All specifications are subject to change without any prior notice .