



VPTZ-1000


Outdoor Speed Dome
Precise, Professional, Competitive




We offer users high quality and competitive products. Our new line of VPTZ1000 speed domes boast industry leading features such as highly precise stepping motors, exact preset points, programmable cruise group and auto scanning etc. Our cost-effective high speed outdoor PTZ's are the perfect choice for your next installation-when it counts.

Features

- Enhanced Spherical Privacy Zone Masking Function
- 1/4" Sony 36X Day/Night zoom camera
- Auto IR Cut Filter Removal (ICR)
- Image Stabilization
- Weather-proof Metal Housing
- High Performance DSP
- Lead Free Electronics
- Dual Fans and Heater
- SMART Lens Control
- 128 preset points
- 8 Cruise Groups
- 2 Private Zones
- Alarm option

Specifications	Sony 36X
Pan	360° Continuous rotation 0.5°/s~280°/s
Tilt	180° auto-flip 0.5°/s~180°/s
Presets	128, rotation speed & idle time programmable
Cruise	8 Group, 16 preset positions for each group
Scanning	Points, scanning speed and idle time programmable
OSD	yes
Privacy Zone Masking	2
Protocols	Videotec, Pelco-P, Pelco-D, Kalatel, Samsung
Control	Rs485
Image Device	sony 1/4" Exview HAD CCD
Effective Picture Elements	380,000 pixels in NTSC
Effective Zoom	432x with optical zoom
Viewing Angle	57.8° (wide end) to 1.7° (tele end)
Minimum Illumination	1/60 sec. mode: 1.4 lux typical (F1.6, 50 IRE) / 1/4 sec. mode: 0.1 lux typical (F1.6, 50 IRE)
Operating Environment	Temperature: -40°C -60°C Humidity: < 90% RH
S/N Ratio	More than 50dB
Shutter Speed	1/1~1/10,000 s, 22 steps
Picture Effects	E-Flip, Nega Art, Black & White, Mirror Image
Camera Operation Switch	Zoom tele, Zoom wide
Video Output	VBS: 1.0 Vp-p (sync negative), Y/C Output
Camera Control Interface	VISCA (TTL signal level), baud rate: 9.6 Kb/s, 19.2 Kb/s, 38.4Kb/s, 1 or 2 Stop bit selectable
Power Requirement	2.4Amps at 24VAC/DC
Contents of Box	Manual, PTZ with Housing, Light weight wall mount, screw driver, clear cover, RS485 connector, DVR CD
Ship Weight	13.4 lbs (6.1kg)
Box Dimensions	12" * 12" * 20" (300mm * 300mm * 500mm)
Cover Options	
Mouning Options	



-  BNC Video Signal Input Port
-  AC24V/DC224V Power Input Port
-  Rs485 Signal Control Port

* All specifications are subject to change without any prior notice .